

Installation Instructions: J-Block or Wide Mount - No Pest Vent

Read all instructions before beginning installation for best results.

The J-Block No Pest Vent nail flange is intended for new construction or when replacing the siding on a building or home.

1. Center the nail flange over the vent hole of the building and secure it in place.
2. Install siding around the nail flange opening.
3. Assemble tube and attach to faceplate with seam oriented up. Be sure all pre-stamped snaps are secure.
4. Insert tube through the nail flange and into the hole in the building. Snap the faceplate into the nail flange, and adjust it to the thickness of the siding.
5. Confirm the faceplate is level, the doors are flush, and closing without issue.

Optional: Seal the top and sides of the faceplate with silicone if needed. Do not seal the bottom as this will not allow the moisture out that collects over time.

IMPORTANT:

Faceplate must be installed level, or slightly inward at the top, so the doors close completely when not in use. An uneven installation will create a poor seal for doors.

If attaching the metal tube to the faceplate the seam MUST be at the top or it will not allow for proper door closer.

Important for Wide Mount Installation

Do not overtighten screws or this will deform the faceplate and the doors will not be flush when closed.

When installing the vent it is important to hang the mounting plate vertical or slightly inward at the top for a better door seal.

The small flat square piece is the inner trim ring. This piece is for trimming around the pipe on the inside on your home or building. We provide this due to the hole possibly being cut larger than the actual size of the vent pipe. If not needed you may recycle it.

Thank you purchasing our J-Block No Pest Vent. We appreciate your business.
P-tec Products, Inc.

Questions

Call: (616) 772-0659

Email: info@p-tecproducts.com